

STAINLESS STEEL HIGH EFFICIENCY COALESCING FILTER *CONTINUED* Series 7130 and 7140

HOW TO ORDER (Filter housings and filter elements are ordered as separate items.)

Model	Port Size	Drain Port	Max. Pressure (psig)	Dimensions (inches)			Filter Element P/N
				A	B	C	
7130-P4FF	1/4" NPTF	1/4" NPTF	1500	0.59	2.36	4.80	25-64-xxx* or SS-130-xx*
7132-P8FF	1/2" NPTF	1/4" NPTF	1500	0.59	2.36	4.80	25-64-xxx* or SS-130-xx*
7132HP-P8FF	1/2" NPTF	1/4" NPTF	3000	0.59	2.52	5.04	25-64-xxx* or SS-130-xx*
7140-P4FF	1/4" NPTF	1/4" NPTF	1500	0.59	2.36	9.29	25-178-xxx* or SS-140-xx*
7142-P8FF	1/2" NPTF	1/4" NPTF	1500	0.59	2.36	9.29	25-178-xxx* or SS-140-xx*
7142HP-P8FF	1/2" NPTF	1/4" NPTF	3000	0.59	2.52	9.53	25-178-xxx* or SS-140-xx*

* Select element from table below.

Elements

P/N	P/N
25-64-70K	SS-130-xx **
25-64-50K	SS-140-xx **
25-178-70K	** Select micron size desired
25-178-50K	

**Size Suffix	Micron Size
01	1
10	10
25	25
100	100

AIR FLOW RATES IN SCFM AT 1.5 PSI PRESSURE DROP

FILTER HOUSINGS USING ELEMENT SIZES 25-64 OR SS-130

Model	Element Grade		Air Pressure (psig)								
	Fluorocarbon	SS	15	30	60	100	150	250	500	1500	3000
7130 Series	50K, 50C	01	64	125	160	256	354	546	1091	3248	-
	70K, 70C	10	87	221	221	354	488	754	1508	4466	-

FILTER HOUSINGS USING ELEMENT SIZES 25-148 OR SS-140

Model	Element Grade		Air Pressure (psig)								
	Fluorocarbon	SS	15	30	60	100	150	250	500	1500	3000
7140 Series	50K, 50C	01	10	15	25	40	55	83	163	488	988
	70K, 70C	10	13	19	32	50	68	106	209	627	1247