TEE PURGE ASSEMBLIES Series 4500

DESCRIPTION


The Series 4500 tee purge assemblies are designed to be installed between the cylinder valve and the pressure regulator. They enable the user to purge the system through the regulator with an inert gas.

The Series 4500 units feature multi-turn diaphragm packless valves and a check valve installed on the purge gas inlet. They are rated for 3000 psig.

HOW TO ORDER

Model	lel Material of Construction			
4510-CGA*	brass			
4520-CGA*	stainless steel			
4550-CGA*	monel® and Al-Si-Bronze			

^{*}Specify CGA connection required when ordering.




Series 4500

TEE PURGE ASSEMBLIES Series 4600

DESCRIPTION

The Series 4600 tee purge assembly was designed for use with inert gases such as argon, helium, and nitrogen. When installed either on the inlet to a pressure regulator or on the cylinder end of a pigtail they are an ideal device for purging the cylinder inlet connection after cylinder changeover to eliminate the introduction of oxygen and water to the system. These tee purges conveniently use the gas in the cylinder for purging.

The Series 4600 can be constructed either with multi-turn or 90° lever actuated diaphragm packless valves. This entire assembly is designed to pass a helium leak rated of 1 x 10^{-8} sccm. They are rated for 3000 psig.



Series 4600

HOW TO ORDER

Mat. of	Connections		
Constr.	Inlet	Outlet	
brass	1/4" NPT female	1/4" NPT female	
brass	1/4" NPT female	1/4" NPT female	
brass	specify CGA	1/4" NPT female	
brass	specify CGA	1/4" NPT female	
brass	specify CGA	1/4" NPT male	
brass	specify CGA	1/4" NPT male	
brass	specify CGA	mating CGA	
brass	specify CGA	mating CGA	
SS	1/4" NPT female	1/4" NPT female	
SS	1/4" NPT female	1/4" NPT female	
SS	specify CGA	1/4" NPT female	
SS	specify CGA	1/4" NPT female	
SS	specify CGA	1/4" NPT male	
SS	specify CGA	1/4" NPT male	
SS	specify CGA	mating CGA	
SS	specify CGA	mating CGA	
	brass brass brass brass brass brass brass brass srass brass brass ss	brass 1/4" NPT female brass 1/4" NPT female brass 5pecify CGA 5prass 5pecify CGA 5prass 5pecify CGA 5p	

^{*}Specify CGA connection required when ordering.