

AUTO-LOGIC® II FULLY AUTOMATIC ELECTRONIC TOUCH SCREEN CHANGEOVER MANIFOLD *CONTINUED*

HOW TO ORDER

Model	Description	Delivery Pressure
918TS-1-200	brass electronic high purity changeover manifold	25-200 psig
918TS-2- 200	stainless steel electronic high purity changeover manifold	25-200 psig

Options

918TSE-email notifies recipient that a changeover has occurred. (Provide email address when ordering.)
 912-AVA audio/visual alarm module for remote alarm
 AVD-45B auto dialer
 914/918-HUB - this hub device allows for multiple dry contact connections to operate auxiliary devices

Pigtails for 918TS Changeover Manifolds (2 per set)

For Brass Manifolds

918-FPB601-Y-CGA*	two flexible Teflon lined stainless steel braided pigtailed with brass fittings and no check valves
918-FPB601-Y-CV-CGA*	two flexible Teflon lined stainless steel braided pigtailed with brass fittings and check valves
918-FPB604-Y-CGA*	two flexible all stainless steel braided pigtailed with brass fittings and no check valves
918-FPB604-Y-CV-CGA*	two flexible all stainless steel braided pigtailed with brass fittings and check valves

For Stainless Steel Manifolds

918-FP604-Y-CGA*	two flexible all stainless steel braided pigtailed without check valves
918-FP604-Y-CV-CGA*	two flexible all stainless steel braided pigtailed with check valves

* Specify CGA connection when ordering.

Y = pigtail length in feet.